



**PARTS LIST**

- |                                     |                            |
|-------------------------------------|----------------------------|
| 2 - HI-LIFT SUPPORT BRACKETS        | 2 - 1/2 SAE FLATWASHERS    |
| 2 - OUTSIDE SUPPORT BRACKETS ( 6" ) | 2 - 1/2 LOCKWASHERS        |
| 2 - INSIDE SUPPORT BRACKETS ( 6" )  | 4 - 3/8 X 2 CARRIAGE BOLTS |
| 2 - 1/2 WING NUTS                   | 4 - 3/8 NYLON LOCKNUTS     |
|                                     | 4 - 3/8 USS FLATWASHERS    |

**INSTALLATION INSTRUCTIONS**

- 1 - INSTALL INSIDE AND OUTSIDE SUPPORT BRACKETS TO ROOF RACK SIDE AS SHOWN.
- 2 - SPACE MOUNTING BRACKETS APPROX 15" TO 18" APPART, SLIGHTLEY TIGHTEN TO HOLD IN PLACE
- 3 - INSTALL HI-LIFT JACK ON THE 1/2 BOLTS THAT COMING OUT OF THE MOUNTING BRACKETS AS SHOWN. ADJUST AND TIGHTEN MOUNTING BRACKET BOLTS, SO THAT THE JACK WILL GO ON AND OFF EASILY.
- 4 - SECURE THE JACK TO THE MOUNTING BRACKETS AS SHOWN AND TIGHTEN.